

# 5500 Lit Rocker Switches - Single Pole 16A 250Vac



- ▶ Standard rocker switch
- ▶ Illuminated
- ▶ Choice of switching circuits
- ▶ Choice of bezel styles
- ▶ Choice of panel cut outs
- ▶ Matching indicator
- ▶ Single pole
- ▶ Splashproof option
- ▶ Bezel size 'A' style 30.2 x 14.0



16(4)A 250Vac T85  
10(3)A 250Vac T100, (12A 250Vac T125 for P rocker only)



UL CSA 15A 250Vac, CSA 16A Non Ind 250Vac  
UL CSA 250Vac 1hp, 125Vac 1/2hp  
UL 85°C, file E45221, CSA file LR10990



Inrush 24A to EN61058-1 & 20A 28Vdc



RoHS compliant

μ contact gap.  
Technical data on pages 4 & 5 (switches), 66 (indicators).  
For Twin units repeat the order details for both the left and right sides.

**C 5503 A L ---**

TERMINAL    FUNCTION    ROCKER    BODY    PRINT, COLOUR, VOLTAGE ETC

▶ TERMINAL	▶ FUNCTION		▶ ROCKER
<p><b>C</b></p> <p>6.3 x 0.8</p>	<p>Approvals &amp; ratings vary with function ON OFF Switches - ON when pressed over terminal 3</p>		<p><b>A</b> Softline (Matt only)</p> <p>Lit</p>
<p><b>H</b></p> <p>4.8 x 0.8</p>	<p><b>5500 μ</b></p>	<p>ON - OFF</p>	<p><b>P</b> Lit window (Matt only)</p> <p>Lit</p>
<p><b>T</b></p> <p>Ø2.1</p> <p>Solder</p>	<p><b>5508 μ</b> for special applications</p>	<p>ON - OFF Lit Unswitched neutral</p>	



C5503AL ---



C5500AL ---



C5503PL ---



C5503A/C5430AL



C5503A/C5503AL



C5503P/C5503PL

**BODY**

**A** Panel cut-outs: 27.2/27.3 height, 12.2/12.3 width, Matt only. Bezel: 30.2 height, 14.0 width.

**B** Panel cut-outs: 30.0/30.1 height, 11.0/11.1 width, Matt only. Bezel: R3.5, 33.4 height, 14.0 width.

**L** Panel cut-outs: 30.0/30.1 height, 11.0/11.1 width, Matt only. Bezel: R1.0, 31.9 height, 14.0 width.

**Q** Panel cut-outs: 28.2/28.3 height, 11.5/11.6 width, Matt. Bezel: R1.6, 30.2 height, 14.0 width.

**R** Panel cut-outs: 28.5/28.6 height, 14.0/14.1 width, Matt only. Bezel: 31.5 height, 17.0 width.

**T** Panel cut-outs: 28.2/28.3 height, 11.5/11.6 width, Matt only. Bezel: R1.6, 30.2 height, 14.0 width.

Cut-outs must be punched in the direction of insertion

**OPTIONS**

**Finish** Matt is standard.

**Colour** Call factory for custom colours. A full range is available for large orders.

**Legend printing** Select from the examples or call factory for custom legends.

**Lamp voltage** Call factory for details.

**Blanking plate A0434 -- (SP) A0494 -- (DP)**  
Dummy units to fill unused panel holes.


**Protective cover** (designed to IP65)  
Snaps on to A, L, Q or T bodies (add G after body in cat no.), this reduces maximum acceptable panel thickness to 1.2mm.



Panel sealing washers W46 (Single Pole) and W42 (Double Pole) are available for these body types, this reduces maximum acceptable panel thickness to 2mm.

For all options call the factory.

**DIMENSIONS (mm)**




Terminal spacing - Poles 10.8 between centres (twin units)

**Panel thickness**

A, Q	0.75 to 3.3mm
L, B, T	0.75 to 2.5mm
R	0.75 to 3.0mm

**Twin units**

Two single switches or a switch and an indicator light can be assembled side by side in one double pole body. For 5500 range panel cut-out details (L, B and T) call factory.



For twin units the first set of order format details refer to the left hand unit, when looking at the front of the assembly. (This has terminal numbers 1, 2 & 3)

**Examples of printing**

