

2000 Slide Switches - up to 5 position 10A 250Vac



- ▶ Slide switches
- ▶ Ratings up to 16A, 250V ac
- ▶ PCB and solder terminals
- ▶ 2, 3, 4 and 5 position
- ▶ Choice of circuits
- ▶ Choice of actuators



10A 250Vac T85
6(3)A 250Vac T85



UL CSA 16A 250Vac Non Inductive
UL CSA 4A 300Vac
UL65°C, file no. E45221, CSA file no. LR10990



RoHS compliant

μ contact gap

Please specify: Standard action (SP116) or Light action (SP118).
2000 series lubrication is inorganic and does not degrade plastics.

Technical data on pages 4 & 5.

T 2 2 20 5 C ---

TERMINAL SERIES POSITIONS CIRCUIT SLIDER BODY PRINT, COLOUR, ETC

TERMINAL	SERIES	POS'N	CIRCUIT <small>Viewed from back</small>	SLIDER
<p>K</p> <p>2.8 x 0.8</p> <p>R</p> <p>2.8 x 0.8</p> <p>T</p> <p>Solder</p> <p>X</p> <p>PCB 0.8 Sq.</p> <p>Y</p> <p>PCB 0.8 Sq. For mounting stability switches have extra "support" terminals</p> <p>* Nominal - Dimension varies with body type. For exact figure call factory</p>	2	2 Switching positions	10	0
			20	6
			30	D
			40	L
			10	1
			20	7
		3 Switching positions	10	E
			20	N
			30	2
			40	9
			10	G
			20	P
4 Switching positions	10	3		
	20	A		
	30	H		
	40	R		
	10	4		
	20	B		
5 Switching positions	10	J		
	20	S		
	30	5		
	40	C		
	10	K		
	20	T		



X22205C ---



T2220EC ---



T23206A ---



T24306A ---



T25302A ---



T25100A ---

BODY


<p>C 2 positions</p>	<p>H 2 positions</p>
<p>A 3 positions</p>	<p>H 3 positions</p>
<p>A 4 positions</p>	<p>H 4 positions</p>
<p>A 5 positions</p>	

OPTIONS


Colour
 For custom slider colours call the factory.
 A full range is available for large orders

DIMENSIONS (mm)


2 Position C body




2 Position H body





Cut-out/PCB Matrix




3 Position A body





3 Position H body



4 Position A body



4 Position H body



5 Position A body

